

## CASING COLLAR LOCATOR - 2 3/4 IN.



**SKU:** 050-CC275-0000

**Categories:** [Cased Hole Wireline](#), [Logging CCLs](#), [Perforating](#), [PTX](#), [Well Intervention](#)

## PRODUCT DESCRIPTION

The Casing Collar Locator (CCL) is used to correlate casing or tubing collars for depth accuracy purposes. The CCL is a dual magnet, center-coil device with a powered amplified signal. This feature provides maximum sensitivity to identify collars in larger casing sizes.

### Ratings & Dimensions

<b>Max Temperature</b>	350°F (177°C)
<b>Max Pressure</b>	20,000 psi (137.9 mPa)
<b>Diameter</b>	2.75 in (69.85 mm)
<b>Length</b>	23.6 in (599.44 mm)
<b>Weight</b>	29.0 lb (13.15 kg)
<b>Tensile Strength<sup>1</sup></b>	<b>Tension:</b> 65,000 lb <b>Compression:</b> 130,000 lb
	<b>Torque:</b> 150 ft-lb

### Hardware Characteristics

<b>Combinability</b>	Corrosion Platform
<b>Tool Positioning</b>	Centralized or Eccentric
<b>Borehole Fluids</b>	Salt, Fresh and Oil

### Electrical Specification

<b>Voltage</b>	100V DC
<b>Current</b>	13mA

### Measurements

<b>Sensor Type</b>	Dual Magnet, Center Coil
<b>Transmission</b>	Line Wobble or Telemetry
<b>Data Rate</b>	20 frames/sec @20 kHz
<b>Principle</b>	Magnetic Flux Line
<b>Diameter Range</b>	3 in (76.2 mm) to 7 in (177.8 mm)
<b>Primary Curve</b>	CCL (mV)

## Connections

<b>Top</b>	1 <sup>3</sup> / <sub>16</sub> " 12P GO box
<b>Bottom</b>	1 <sup>3</sup> / <sub>16</sub> " 12P GO pin

<sup>1</sup>Strengths apply to new tools at 70°F (21°C) and 0 psi.

Version Control: 2022.02.28

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***