

## MOTORIZED EJECTOR TOOL - PTX - 1 3/8 IN.



SKU: 050-E1375-0000

Categories: [Cased Hole Wireline](#), [Leak Detection](#), [Production Logging](#), [PTX](#)

## PRODUCT DESCRIPTION

This Motorized Ejector Tool is typically used with a Gamma Ray and Casing Collar Locator (CCL) tool to determine flow conditions, flow profiles, fluid flow, fluid injection and production rates.

The tool discharges a short half-life radioactive iodine fluid into the well bore. Information from the Gamma Ray Tool in the string can also be used to assist in the location of leakage in pipes, across packers and fluid movement behind production strings.

### Ratings & Dimensions

<b>Max Temperature</b>	350°F (177°C)
<b>Maximum Pressure</b>	20,000 psi (138 MPa)
<b>Outer Diameter</b>	1.38 in (35.1 mm)
<b>Length</b>	26.5 in (673.1 mm)
<b>Weight</b>	8 lb. (3.64 kg)
<b>Materials</b>	Standard or Titanium Available

### Borehole Conditions

<b>Borehole Fluids</b>	Salt, Fresh and Oil
<b>Tool Positioning</b>	Centralized & Eccentralized

### Hardware Characteristics

<b>Connections</b>	<b>Top:</b> 1 <sup>3</sup> / <sub>16</sub> " 12P type "A" GO box <b>Bottom:</b> 1 <sup>3</sup> / <sub>16</sub> " 12P pin (w/ no electrical feed-thru)
<b>Combinability</b>	1 <sup>3</sup> / <sub>16</sub> " 12P type "A" GO pin (w/ feed-thru) Temperature   Casing Collar Locator   Gamma Ray

## Electrical Specification

**Voltage**

100V DC

Version Control: 2022.02.10

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***