

FIXED CAGE SPINNER MECHANICAL - HD - 1 11/16 IN.



SKU: FCSM01, FCSM02 and FCSM04

Categories: [Cased Hole Wireline](#), [Fluid Velocity](#), [HD Platform™](#), [Production Logging](#)

PRODUCT DESCRIPTION

The Fixed Cage Spinner Mechanical (FCSM01,02,04) is run in combination with the 1 11/16 inch FLTE (Flow & Temperature Electronics) which combines the flowmeter sensor electronics with a fast response temperature tool or with our 1 11/16 inch CFT (combined Capacitance, Flow & Temperature) tool. The size is selected depending on the minimum restriction in the completion. The impeller assembly is protected minimizing the likelihood of damage in hole.

Ratings & Dimensions

	FCSM01	FCSM02	FCSM04
Max temperature	350°F (177°C)		
Max pressure	15,000 psi (103.4 mPa)		
Cage diameter	1.69 in (43.0 mm)	2.13 in (54 mm)	3.15 in (80 mm)
Length	6.5 in (165 mm)	6.9 in (175 mm)	7.5 in (191 mm)
Weight	1.4 lb (0.65 kg)	1.6 lb (0. kg)	2.2 lb (1 kg)
Materials	Corrosion resistant materials used throughout		

Measurements

Output	10 pulses per revolution
Threshold	<5 ft/min (1.5 m/min)
Range	Better than 1,500 ft/min
Maximum RPS	200 rps - 4,000 ft/min (measured by FLTE or CFT)

Hardware Characteristics

Combinability	All HD tools (RADii, iQ, PL, RAS, etc.) when connected to FLTE & CFT
----------------------	--

ONLINE TECHNICAL SPECIFICATION SHEET



Acquisition Mode

Real-time (with TCU)

Memory (with MLT)

Version Control: 2021.11.17

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.