


## MEMORY BATTERY SUB - HD - 1 11/16 IN.



**SKU:** MBS003 or MBS004

**Categories:** [Cased Hole Wireline](#), [HD Platform™](#), [Memory](#)

## PRODUCT DESCRIPTION

The Memory Battery Sub (MBS003,004) is used in conjunction with the Memory Logging Tool (MLT002). The tool houses the battery pack.

### Ratings & Dimensions

<b>Diameter</b>	1.69 in (43.0 mm)
<b>Max temperature*</b>	392°F (200°C)
<b>Max pressure</b>	15,000 psi (103.4 mPa)
<b>Materials</b>	Corrosion resistant materials used throughout

### Hardware Characteristics

<b>Combinability</b>	All HD tools (RADii, iQ, PL, RAS etc)
<b>Upper Connection</b>	$1\frac{5}{16}$ " UN thread

### Electrical Specifications

	<b>MBS003</b>	<b>MBS004</b>
<b>Battery pack</b>	5 x C cell	5 x CC cell
<b>Nominal</b>	19.5 V	
<b>Cell voltage</b>	3.9 V	
<b>Chemistry</b>	Lithium Sulfuryl Chloride	
<b>Discharge</b>	3% per year at 77°F (25°C)	
<b>Temperature Range</b>	-4°F to 320°F (-20°C to 160°C)	

\* Batteries is not included.

\* Temperature range is determined by the battery pack. Typical battery packs are rated between -4°F to 320°F (-20°C to 160°C).



Version Control: 2021.11.11

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***