

IQ™ MAGNETIC PROPERTIES TOOL - HD - 3 1/2 IN.



SKU: 050-CI350-1100

Categories: [Cased Hole Wireline](#), [Electro-Magnetic Thickness](#), [HD Platform™](#), [iQ™](#), [Well Integrity](#)

PRODUCT DESCRIPTION

The 4-segment receiver of the iQ™ HD Magnetic Properties Tool measures the casing in 90° sections (quadrants). The tool produces a magnetic field that opposes the primary field casing attenuation and phase shift. The magnitude of the measured phase shift is a function of the electrical conductivity, magnetic permeability and metal thickness of the field being measured. Multiple coil spacing and frequencies control the depth of investigation and measure the electromagnetic properties of the casing, that yield a quantitative casing thickness and internal diameter measurements.

Ratings & Dimensions

Max Temperature	350°F (177°C)
Maximum Pressure	15,000 psi (103.42 MPa)
Outer Diameter	3.5 in (69.85 mm)
Length	68.4 in (1737.36 mm)
Weight	130.0 lb (177.0 kg)
Csg/Tbg OD	Min: 4.5 in (114.3 mm) Max: 9.625 in (244.46 mm)
Tensile Strength	Tension: 15,000 lb Compression: 15,000 lb
Measure Points	Thickness: 32.66 in (829.6 mm) Caliper: 25.62 in (650.8 mm)

Borehole Conditions

Tool Positioning	Centralized
-------------------------	-------------

Hardware Characteristics

Source Type:	Single and multi frequency AC coils Azimuthal thickness gauge with quadrant sensitivity
Sensor Type	Multi-frequency caliper and casing properties 3-axis accelerometer for tool orientation

Connections	E-Line 'GO' Type
Combinability	GR, CCL, ProMAC, Rarii
Acquisition Mode	SRO w/ TCU Mem w/ MLT

Electrical Specification

Current	+ 45 mA @ 130V
----------------	----------------

Version Control: 2021.11.17

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.