


SHOOTING CASING COLLAR LOCATOR - AES - 2 1/8 IN.



SKU: SCL003

Categories: [Cased Hole Wireline](#), [Perforating](#), [PTX](#), [Shooting CCLs](#), [Well Intervention](#)

PRODUCT DESCRIPTION

Ratings & Dimensions

| | |
|-------------------------|----------------------|
| Max Temperature | 350°F (177°C) |
| Maximum Pressure | 20,000 psi (138 MPa) |
| Outer Diameter | 2.125 in (53.98 mm) |
| Length | 18.50 in (469.9 mm) |
| Weight | 26.0 lb (11.8 kg) |

Borehole Conditions

| | |
|------------------------|---------------------|
| Borehole Fluids | Salt, Fresh and Oil |
|------------------------|---------------------|

Hardware Characteristics

| | |
|---------------------|---|
| Connections* | Top: 1 3/16" 12P GO Box Bottom: 1 3/16" 12P GO Box |
|---------------------|---|

Electrical Specification

| | |
|---------------------|-------|
| Voltage (DC) | 130V |
| Current | 22 mA |

Measurements

| | |
|--------------------------|-------------------------|
| Data Transmission | Analog, Line Wobble, mV |
|--------------------------|-------------------------|

*Alternative connections available upon request.

Version Control: 2022.02.28

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.