

## 3-ARM CALIPER TOOL - PTX - SLIM PL SUITE - 1 3/8 IN.



**SKU:** 050-C1375-0001

**Categories:** [Caliper](#), [Cased Hole Wireline](#), [Production Logging](#), [PTX](#), [Slim PL](#)

## PRODUCT DESCRIPTION

The motorized 3-Arm Caliper tool is used to measure borehole diameter with excellent accuracy, stability, and repeatability. Can be used for locating packer seats, collapsed tubing or casing, as well as any other internal measurement that might be required throughout the life of a well bore.

### Ratings & Dimensions

<b>Max Temperature</b>	350°F (177°C)
<b>Max Pressure</b>	20,000 psi (137.9 mPa)
<b>Diameter</b>	1.38 in (35.052 mm)
<b>Length</b>	37.5 in (952.5 mm)
<b>Weight</b>	10.0 lb (4.5 kg)

### Hardware Characteristics

<b>Combinability</b>	1.38 in Production Logging Tools (CCL/Temp/GR)
<b>Tool Positioning</b>	Centralized

### Electrical Specification

<b>Voltage</b>	<b>Operating:</b> 75V DC   <b>Motoring:</b> 30V
<b>Current</b>	60mA

### Caliper Measurements

<b>Resolution</b>	± 3% of reading (at mid-range extension)
<b>Diameter Range</b>	2.0 in (50.8 mm) to 15.0 in (381.0 mm)

### Connections

<b>Top</b>	1 <sup>3</sup> / <sub>16</sub> " 12P type "A" GO box
<b>Bottom</b>	1 <sup>3</sup> / <sub>16</sub> " 12P type "A" GO box (with feed through)
	1 <sup>3</sup> / <sub>16</sub> " 12P Pin (with no feed through)

Version Control: 2022.01.04

---

***On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.***