

INTELLEX™ EBW LOW POWER ELECTRONIC TRIGGER - 1 3/8 & 1 11/16 IN.



SKU: SEN-0010-0316 and SEN-0010-0307

Categories: [Cased Hole Wireline](#), [Firing Heads - Triggers](#), [Intellex™](#), [Perforating](#), [PTX](#), [Well Intervention](#)

PRODUCT DESCRIPTION

Intellex™ EBW Low Power Electronic Triggers are battery powered low power electronic firing heads used to initiate the detonation of ballistic devices with the highest degree of safety and control.

Ratings & Dimensions

Tool type	1.375 OD Firing Head	1.69 OD Firing Head
Part Number	SEN-0010-0316	SEN-0010-0307
Max temperature	347°F (175°C)	
Max pressure	15,000 psi (103.4 mPa)	
Outer diameter	1.375 in (34.9 mm)	1.690 in (43.0 mm)
Length	46.0 in (1.17 m)	
Weight	22.0 lbs (9.9 kg)	
Max Tensile Load	20,000 lbs (9,000 kgs)	30,000 lbs (13,600 kgs)
Materials	Corrosion resistant materials used throughout	

Hardware Characteristics

Housing Connection	17-4PH (standard) or NACE MR-01-75 Compatible Top: 15/16 in x 10 UN (5/8 in Sucker Rod) Bottom: 1 3/16 in x 12 UNF GO Pin
Supported Devices	EBW Detonators and Igniters using Ecosse EBW Firesets Resistorized detonators using EBW & CDM module

Temperature Measurements

Range	0 - 165°C (32- 329°F)
--------------	------------------------

Accuracy < $\pm 0.5^{\circ}\text{C}$
Resolution < 0.01°C @ 1 sps

Pressure Characteristics

Range 0 - 15000psi (0 - 103.42MPa)
Accuracy < $\pm 0.05\%$ FS
Resolution 0.01 psi @ 10,000 psi & 1 sps

Acceleration

Accuracy ± 0.1 g
Resolution < 0.01 g

Electrical Specification

	Module A	Module C & D
Battery	2 x PMX165 'C' Lithium battery	
Voltage (DC)	5-9Vdc, power supplied via USB or 2 x 'C' cell Lithium battery pack.	
Memory Rate	145.5 hrs/6.06 days @ 1 sps	18.2 hrs/0.75 days @ 1 sps
	Modules C & D can be sampled at slower speeds allowing up to 30 days logging. EFH will continue to function even if the memory is full.	
Consumption	10mA Max Logging, 2A Max Firing Current	
Shock	> 500 g	
Shooting CCL	500 μA (Idle); 8 sps, stored 1 sps to memory	

Version Control: 2022.02.15

On-line specifications are for REFERENCE ONLY and subject to change without notice. DO NOT USE FOR FIELD OPERATIONS.